

 **GREE**  
AIR CONDITIONER

*Window/Wall  
Air Conditioner*



Find out more at [www.greeac.com.au](http://www.greeac.com.au)

**6**   
YEAR  
WARRANTY

## Wireless Remote Control

---

- **Auto**  
Operation is selected based on current room temperature.
- **Cooling plus Energy Saver Mode**  
Energy saver mode switches the fan off once the air conditioner has reached the set point of the thermostat.
- **Drying/Dehumidifying**
- **Heating**
- **Fan Only**

Heating and cooling capacities are based on AS/NZ 3823.1.1.

Running current is rated at AS/NZ 3823.1.1 standards and does not include compressor start-up or power supply variations. Failure to comply with relevant Government regulations may void the warranty.

Due to continuous product improvements, specifications are subject to change without prior notice.

(Excludes GJC05AI)





## Features

- 3-Speed Fan, with Auto Mode**  
 In auto the fan speed automatically adjusts as the room temperature changes.
- Fresh Air Ventilation**  
 Adjust the slider to ventilate and expel smoke and odours from the room.
- Anti-Corrosion Protection Features**  
 Hydrophilic Blue Fin Coils. Galvanised and painted slide out chassis.
- Digital Display with On/Off Button\*1**  
 If the remote is lost the air conditioner can be run via the digital control panel on the unit. The unit display can be turned off via the remote control.
- Self-Diagnostics**  
 In the unlikely event of a malfunction, the malfunction code will be displayed aiding a speedy repair.
- Check Filter Indicator**  
 This feature is a reminder to clean the filter for more efficient operation. The LED light will illuminate after 250 hours of operation.
- Auto Swing Air Direction**  
 When the swing button is pressed on the remote control the air direction louvres will start to rotate automatically. Press the swing button again to stop and set at the desired direction.
- Clock with On/Off Timer**  
 The clock must be set on the remote control to enable the timer to be set to come on or turn off at a certain time.
- Sleep Function**  
 The sleep function changes the set point temperature after one and then two hours. This follows a more natural sleep pattern.



3D Airflow



Comfortable Sleep Curves



Fresh Air Supply Ventilation



Cold Air Prevention



Timer



Self-diagnosis



Auto Restart



Automatic Operation



Wifi Control \*2

\*1 Excludes GJCO5AI

\*2 Excludes GJCO5AI

### Reverse Cycle

Model	GJH07AK-K6NRNG2A	GJH09AK-K6NRNG2A	GJH12AG-K6NRNG1A	GJH18AE-K6NRNG1A	GJH21AE-K6NRNG1A	
Part Number	AC5055	AC5056	AC5057	AC5058	AC5059	
<b>Performance</b>						
Cooling Capacity	kW	2.2	2.7	3.9	5.3	6
Heating Capacity	kW	1.9	2.45	3.6	4.8	5.5
Cooling Power Input	W	660	825	1180	1600	1810
Heating Power Input	W	570	740	1060	1450	1690
AEER	W/W	3.33	3.33	3.31	3.31	3.31
ACOP	W/W	3.33	3.31	3.4	3.31	3.26
Cooling Energy Stars (Hot/Average/Cold)	No.	2/1.5/2	2/1.5/2	1.5/1.5/1.5	2/1.5/1.5	1.5/1.5/1.5
Heating Energy Stars (Hot/Average/Cold)	No.	1/1/0.5	1/1/0.5	1/1/0.5	1/0.5/0.5	1/0.5/0.5
Dehumidifying Volume	L/Hr	1	1	1.5	2.2	2.2
Air Flow Volume (Max)	m3/h	480	480	660	780	840
SPL (Max) Indoor	dB (A)	50	50	50	55	56
SPL Outdoor	dB (A)	57	57	60	63	64
<b>Electrical</b>						
Power Supply	220 - 240V 50Hz					
Recommended Circuit Breaker	A	10	10	10	15	15
Cooling / Heating	A	2.87/2.48	3.63/3.25	5.13/4.53	7.87/7.35	7.87/7.35
<b>Dimensions and Weights</b>						
Dimension (W×H×D)	mm	560x375x668	560x375x668	660x428x700	660x428x770	660x428x770
Net Weight	kg	36	40	51	64	65
<b>Installation</b>						
Operating Temperature Range	°C	-7~43				
Refrigerant	R32					
Refrigerant Charge	kg	0.43	0.43	0.73	0.8	0.8

### Cooling Only

Model	GJC05AI-K6NMNG3A	GJC07AK-K6NRNG2A	GJC09AK-K6NRNG2A	GJC12AG-K6NRNG1A	GJC18AE-K6NRNG1A	GJC21AE-K6NRNG1A	
Part Number	AC5078	AC5080	AC5082	AC5084	AC5086	AC5088	
<b>Performance</b>							
Cooling Capacity	kW	1.6	2.2	2.7	3.9	5.6	6
Cooling Power Input	W	480	660	825	1180	1600	1810
AEER	W/W	3.3	3.33	3.31	3.31	3.31	3.31
Cooling Energy Stars (Hot/Average/Cold)	No.	2/1.5/1.5	2/1.5/2	2/1.5/2	1.5/1.5/1.5	2/1.5/1.5	1.5/1.5/1.5
Dehumidifying Volume	L/Hr	1.15	1	1	1.5	2.2	2.2
Air Flow Volume (Max)	m3/h	370	480	480	640	780	860
SPL (Max) Indoor	dB (A)	49	50	50	50	55	56
SPL Outdoor	dB (A)	56	57	57	60	63	64
<b>Electrical</b>							
Power Supply	220 - 240V 50Hz						
Recommended Circuit Breaker	A	10	10	10	15	15	15
Cooling / Heating	A	2.4	2.87	3.63	5.13	6.96	7.87
<b>Dimensions and Weights</b>							
Dimension (W×H×D)	mm	450x350x580	560x375x668	560x375x668	660x428x700	660x428x770	660x428x770
Net Weight	kg	29	36	40	51	64	65
<b>Installation</b>							
Operating Temperature Range	°C	18~43					
Refrigerant	R32						
Refrigerant Charge	kg	0.35	0.36	0.41	0.55	0.7	0.78

Note: Above parameters are for reference only. Actual parameter may vary.



For Installation and Sales:

For Parts and Warranty:

www.greeonline.com  
 0800 BUY GREE (NZ)  
 1800 GREE 4 ME (AU)



1800 GREE 4 ME  
 1800 47334 63